

Rust Preventatives - keywords:

Rust preventative, long term, water based, oil based, solvent based

See products fact sheets below.

1 Description:

TechPro FT 1001 is a water soluble rust preventive that leaves a light, dry/soft waxy film that when added direct provides up to one year of indoor protection. TechPro FT 1001 can be used as an addition to coolant or drawing compound systems extending the corrosion protection. TechPro FT 1001 can be removed with a light alkaline cleaner.

This post is also available in: Spanish

Typical Properties (Not Specifications):

Appearance	Clear light amber liquid
Density (lbs/gal)	8.51
Viscosity (cSt)	5

Health & Safety

TechPro FT 1001 is available in 55 gallon drums, 330 gallon totes and bulk tanker truck.

Storage and Handling: See Material Safety Data Sheet Before Use. Use at room temperature. If frozen, allow to thaw completely prior to use. Do not expose to extreme high temperature due to drum rupture. Do not pressurize drum or reuse empty container.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Features / Benefits

- Offers 12-month indoor rust protection
- Can be added to coolant or drawing compounds to extend corrosion protection
- Easily applied
- Non staining
- Can be applied to all substrates
- Dry to touch
- Easily removed with light alkaline cleaner

Mix / application & Use

Used direct to parts at 5 to 10% added to water.

When mixing into a coolant or drawing compound add TechPro FT 1001 between 2-5%.

2 **Description:**

TechPro FT 1005 is a synthetic, heavy-duty, ready to use, rust preventative. TechPro FT 1005 leaves a light, dry/soft waxy film that provides up to 12-month indoor protection. TechPro FT 1005 Can be used as an addition to cooling systems or applied direct to the part. TechPro FT 1005 can be removed with a light alkaline cleaner.

This post is also available in: Spanish

Typical Properties (Not Specifications):

Appearance	Tan opaque emulsion
Density (lbs/gal)	8.34

Health & Safety

TechPro FT 1005 is available in 55 gallon drums, 330 gallon totes and bulk tanker truck.

Storage And Handling: See Material Safety Data Sheet Before Use. Use at room temperature. If frozen, allow to thaw completely prior to use. Do not expose to extreme high temperature due to drum rupture. Do not pressurize drum or reuse empty container.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Features / Benefits

- Offers 12-month protection
- Easily applied
- Non Staining
- Can be applied to all substrates
- Dry to touch
- Easily removed with light alkaline cleaner

Mix / application & Use

Used direct to parts at 5 to 10% added to water.

When mixing into a coolant or drawing compound add TechPro FT 1001 between 2-5%.

3 **Description:**

TechPro FT 1010 is a heavy-duty, ready to use rust preventative. TechPro FT 1010 leaves a light residue that provides up to two years of indoor protection. TechPro FT 1010 can be applied direct to the part by spray, drip or brush. TechPro FT 1010 can be removed with a light alkaline cleaner.

This post is also available in: Spanish

Typical Properties (Not Specifications):

Appearance	Clear light amber liquid
Density (lbs/gal)	6.84
Viscosity (cSt @ 40C)	6

Health & Safety

TechPro FT 1010 is available in 55 gallon drums, 330 gallon totes and pails.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. If frozen, allow to thaw completely prior to use. Do not expose to extreme high temperature due to drum rupture. Do not pressurize drum or reuse empty container.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Features / Benefits

- Offers two years of indoor protection
- Easily applied
- Non Staining
- Can be applied to all substrates
- Very light residue
- Easily removed with light alkaline cleaner
- Flash Point >200F

Mix / application & Use

Use as is. May be applied by spray, dip or brush.

4 **Description:**

TechPro FT 1015 is an oil-based, heavy-duty rust preventative. TechPro FT 1015 offers two-year indoor protection and can be applied directly to the part with spray, dip or brush techniques. TechPro FT 1501 can be removed with a light alkaline cleaner.

This post is also available in: Spanish

Typical Properties (Not Specifications):

Appearance	Clear dark amber liquid
Density (lbs/gal)	7.76
Viscosity (cSt @ 40C)	60

Health & Safety

TechPro FT 1015 is available in 55 gallon drums, 330 gallon totes and bulk tanker truck.

Storage and Handling: See Material Safety Data Sheet Before Use. Use at room temperature. If frozen, allow to thaw completely prior to use. Do not expose to extreme high temperature due to drum rupture. Do not pressurize drum or reuse empty container.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Features / Benefits

- Offers two-year protection
- Easily applied
- Non Staining
- Can be applied to all substrates
- Oily residue
- Easily removed with light alkaline cleaner

Mix / application & Use

Apply direct to substrate using spray, dir or brush applications.

5 Description:

TechPro FT 1010 is a heavy-duty, ready to use rust preventative. TechPro FT 1010 leaves a light residue that provides up to two years of indoor protection. TechPro FT 1010 can be applied direct to the part by spray, drip or brush. TechPro FT 1010 can be removed with a light alkaline cleaner.

This post is also available in: Spanish

Typical Properties (Not Specifications):

Appearance	Clear light amber liquid
Density (lbs/gal)	6.84
Viscosity (cSt @ 40C)	6

Health & Safety

TechPro FT 1010 is available in 55 gallon drums, 330 gallon totes and pails.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. If frozen, allow to thaw completely prior to use. Do not expose to extreme high temperature due to drum rupture. Do not pressurize drum or reuse empty container.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Features / Benefits

- Offers two years of indoor protection
- Easily applied
- Non Staining
- Can be applied to all substrates
- Very light residue
- Easily removed with light alkaline cleaner
- Flash Point >200F

Mix / application & Use

Use as is. May be applied by spray, dip or brush.